



MSDS - 3600EX

MATERIAL SAFETY DATA SHEET

Product Identifier Firestop 3600EX
Product Use Fire and Smoke Stop Intumescent Caulk
Manufacturer Passive Fire Protection Partners, 1412 Derwent Way, Delta, BC V3M 6H9
Emergency Number (800) 810 - 1788

INGREDIENT INFORMATION

Ingredient	CAS #	% (wt.)	LC ₅₀ (rat)	LD ₅₀ (rat)	TLV	STEL
Calcium Carbonate	1317-65-3	< 50	N/A	N/A	N/A	N/E
Acrylic Polymer	None known	< 45	N/A	N/A	N/A	N/A
Water	7732-18-5	< 25	N/A	N/A	N/E	N/E
Graphite	7782-42-5	< 10	N/A	N/A	2.0 mg/m ³	N/A
Auxiliary Chemicals	N/A	< 10	N/A	N/A	N/A	N/A
Iron Red Oxide ⁽¹⁾	1309-37-1	< 0.5	N/A	N/A	N/A	N/A
Iron Black Oxide ⁽²⁾	1317-61-9	< 0.1	N/A	N/A	N/A	N/A
Titanium Dioxide ^{(3),(4)}	13463-67-7	< 2	N/A	N/A	10 mg/m ³	N/A
Iron Yellow Oxide ⁽⁴⁾	51274-00-1	< 1	N/A	N/A	N/A	N/A
Aqueous Colorant, Blue ⁽⁵⁾	N/A	< 0.5	N/A	N/A	N/A	N/A

(1) - Rust Red; (2) - Grey; (3) - White; (4) - Yellow; (5) - Blue

PHYSICAL PROPERTIES

Appearance / Physical State	Rust Red, viscous compound	Specific Gravity (@25°C)	1.40 – 1.50
Odour	Mild odour	Evaporation Rate	< 1
Odour Threshold	Slight aromatic odour	Boiling Point (°C)	> 100
Vapour Pressure (mm Hg)	N/A	Freezing Point (°C)	0
Vapour Density (Air = 1)	of Water vapour	pH	8.0 - 9.0
Coefficient of H₂O/Oil Distrib	Not determined	VOC contents (g/L)	37.1

FIRE AND EXPLOSION DATA

Flammability	No
Means of Extinction	Normal fire fighting procedures should be followed to avoid inhalation of smokes and gases.
Special Fire-fighting Procedures	Firefighters should wear the usual protective gear use self-contained breathing apparatus.
Auto-ignition Temperature (°C)	N/A
Flash Point (°C) / Method	N/A
Upper Flammable Limit (% Vol.)	N/A
Lower Flammable Limit (% Vol.)	N/A
Sensitivity to Mechanical Impact	No
Sensitivity to Static Discharge	No
Hazardous Combustion Products	Carbon Monoxide, Carbon Dioxide, Aliphatic Hydrocarbons and Hydrocarbon Oxidation products.

MSDS - 3600EX





REACTIVITY DATA

Stability	Stable under normal storage conditions
Condition of Reactivity	Contact with incompatible substances.
Incompatible Materials	Reacts with mineral acids and alkalis
Hazardous Decomposition Products	Dried film forced to burn will produce: Carbon Monoxide, Carbon Dioxide, Aliphatic Hydrocarbons and Hydrocarbon Oxidation products. .

TOXICOLOGICAL PROPERTIES

Routes of Exposure	<input checked="" type="checkbox"/> Skin contact	<input type="checkbox"/> Skin absorption	<input type="checkbox"/> Eye contact	<input type="checkbox"/> Inhalation	<input type="checkbox"/> Ingestion
Effects of Acute Exposure to Product	Skin and eyes irritation may occur after contact with the product.				
Effects of Chronic Exposure to Product	None known				
Exposure Limits	None known				
Irritancy of Product	Slight on skin				
Sensitization of Product	None known				
Carcinogenicity	None known				
Teratogenicity	None known				
Reproductive Toxicity	None known				

FIRST AID MEASURES

Eye Contact	Flush eyes with large quantities of water for 15 minutes and get medical attention.
Skin Contact	Wash with soap and water.
Inhalation	Remove affected person away from source of exposure to fresh air and get medical attention IMMEDIATELY.
Ingestion	Get medical attention IMMEDIATELY.

PREVENTIVE MEASURES

Engineering Controls	Standard industrial ventilation is recommended.
Personal Protective Equipment	Chemical safety glasses and gloves were required during normal use and handling.
Eye Protection (Specify)	Face shield or chemical goggles were recommended.
Skin Protection (Specify)	Chemical resistant nitrile, neoprene or rubber gloves were recommended if contact to the product directly.
Respiratory (Specify)	Respiratory protection is not normally required. Use a NIOSH/MSHA approved respirator if conditions warrant.
Other	

PRECAUTION FOR SAFE HANDLING AND USE

Handling Procedure and Equipment	N/A
Storage Requirement	Material should be kept in original closed container and stored between 4-32°C (40-90°F).
Spill, Leak or Releases	Wear protective equipment during cleanup.
Waste Disposal	Care should be taken to ensure that the material or its containers and disposed of in an approved facility, state, provincial and local regulations.
Special Shipping Instructions	DO NOT FREEZE

MSDS - 3600EX





MSDS - 3600EX

REGULATION INFORMATION

WHMIS	Not controlled
HMIS	Health 1, Flammability 0, Reactivity 0
TDG Regulation	Not classified as a hazardous material
TSCA	All ingredients of this product are on the inventory list.
DSL	All ingredients of this product are on the list.

PREPARATION INFORMATION

Prepared by	Chemical Laboratory, Passive Fire Protection Partners
Date of Issue	January 03, 2003
Telephone	(604) 515-1788
Website	www.firestop.com
Reason for Revision	New formulation, rev 001, January 03, 2003 Ingredient information updating, rev 002, November 16, 2006 Formulation updating, rev 003, August 24, 2009 Spelling mistake on Section of Precaution fro Safe Handling and Use, rev 004, March 1, 2010 MSDS format change, rev 005, September 24, 2012
Revision Date	September 22, 2016
Abbreviations Used	% (wt.) = Weight Percentage ACGIH = American Conference of Governmental Industrial Hygienists CAS Number = Chemical Abstracts Series Number DSL = Domestic Substance List in Canada H = Hours HMIS = Hazardous Material Identification System IARC = International Agency for Research on Cancer LC₅₀ = Lethal Concentration, 50% LD₅₀ = Lethal Dose, 50% MSHA = Mine Safety and Health Administration N/A = Not Applicable or Not Available N/E = None Established NIOSH = The National Institute for Occupational Safety and Health NTG = National Toxicology Program OSHA = The Occupational Safety and Administration STEL = Short Term Exposure Limit TDG = Transportation of Dangerous Goods TLV = Threshold Limit Value TSCA = Toxic Substance Control Act in US VOC = Volatile Organic Compounds WHMIS = Workplace Hazardous Material Identification System

This information is provided in good faith and is correct to the best of PFP Partners' knowledge as of the date hereof; however, PFP Partners makes no representation as to its completeness or accuracy. Customers are encouraged to make their own determination as to the suitability of this product for their purpose prior to use. PFP Partners disclaims responsibility to damages of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.

MSDS - 3600EX

