

009

MATERIAL SAFETY DATA SHEET

Product Identifier Product Use Manufacturer Emergency Number	Firestop 4100SL Fire and Smoke Stop Self Leveled Sealant Passive Fire Protection Partners, 1412 Derwent Way, Delta, BC V3M 6H9 (800) 810 - 1788					
INGREDIENT INFORMATION						
Ingredient Calcuim Carbonate	CAS # 1317-65-3	% (wt.) < 50	LC₅₀ (rat) N/A	LD₅₀ (rat) N/A	TLV N/A	STEL N/E
Water	7732-18-5	< 35	N/A	N/A	N/E	N/E
Vinyl Acetate Polymers	25067-01-0	< 30	N/A	N/A	N/A	N/A
Additives	N/A	< 5	N/A	N/A	N/A	N/A
Vinyl Acetate Monomer	108-05-4	< 0.1	11400 mg/m³/4H	2900 mg/Kg	10 ppm	N/A
Iron Red Oxide ⁽¹⁾	1309-37-1	< 1	N/A	N/A	N/A	N/A

PHYSICAL PROPERTIES					
Appearance / Physical State	Red, viscous compound	Specific Gravity (@25°C)	1.20 – 1.50		
Odour	Mild odour	Evaporation Rate	< 1		
Odour Threshold	Slight aromatic odour	Boiling Point (°C)	> 100		
Vapour Pressure (mm Hg)	17.35	Freezing Point (°C)	0		
Vapour Density (Air = 1)	of Water vapour	рН	8.0 - 10.0		
Coefficient of H ₂ O/Oil Distrib	Not determined.	VOC contents (g/L)	26.0		

FIRE AND EXPLOSION DATA

Flammability Means of Extinction	No Normal fire fighting procedures should be followed to avoid inhalation of smokes and gases.
Special Fire-fighting Procedures	Firefighters should wear the usual protective gear, including the use of self-contained breathing apparatus.
Auto-ignition Temperature (°C)	N/A
Flash Point (°C) / Method	N/A
Upper Flammable Limit (%, Vol.)	N/A
Lower Flammable Limit (%, Vol.)	N/A
Sensitivity to Mechanical Impact	No
Sensitivity to Static Discharge	No
Hazardous Combustion Products	Carbon Monoxide and/or Carbon Dioxide

Recycled Recyclable



1.800.810.1788 Technical Support 1.800.810.1788 Customer Service

© 2017 PFP Partners. All rights reserved.

www.firestop.com email: firestop@firestop.com **Passive Fire Protection Partners** 1412 Derwent Way Delta, BC V3M 6H9



	REACTIVITY DATA			
Stability	Stable under normal storage conditions			
Condition of Reactivity	Contact with incompatible substances.			
Incompatible Materials	Reacts with strong acids and liberates carbon dioxide			
Hazardous Decomposition Products	Dried film forced to burn will produce: Carbon Monoxide, Carbon Dioxide and Hydrocarbon Oxidation products.			
Floducts	TOXICOLOGICAL PROPERTIES			
Routes of Exposure Skin	□ Skin □ Eye contact □ Inhalation □ Ingestion			
contac				
Effects of Acute Exposure to Product	Skin and eye irritation may occur after contact with the product.			
Effects of Chronic Exposure to	None known			
Product				
Exposure Limits	10 ppm for vinyl acetate monomer (ACHIH)			
Irritancy of Product	Slight on skin and eyes			
Sensitization of Product	None known			
Carcinogenicity	OSHA, NTP and ACGIH have not classifed this product as a carcinogen. However, Vinyl Acetate is identified by IARC as a potential carcinogen			
	on testing on laboratory animals, but there is no evidence that it has			
	caused cancer in human.			
Teratogenicity	None known			
Reproductive Toxicity	None known			
	FIRST AID MEASURES			
Eye Contact	Flush eyes with large quantities of water for 15 minutes and get			
Skin Contact	medical attention. Wash with soap and water immediately.			
Inhalation	Remove affected person away from source of exposure to fresh air and			
	get medical attention IMMEDIATELY.			
Ingestion	Get medical attention IMMEDIATELY.			
	PREVENTIVE MEASURES			
Engineering Controls	General ventilation is recommended during normal use.			
Personal Protective Equipment	Not required. during normal use and handling.			
Eye Protection (Specify)	Face shield or chemical goggles are recommended .			
Skin Protection (Specify)	Chemical resistant nitrile, neoprene or rubber gloves are recommended			
Respiratory (Specify)	if contact to the product directly. Respiratory protection is not normally required. Use a NIOSH/MSHA			
	approved respirator if conditions warrant.			
Other				
PRECAUTION FOR SAFE HANDLING AND USE				
Handling Procedure and	N/A			
Equipment				
Storage Requirement	Material should be kept in original closed container and stored between			
Spills, Leaks or Releases	4-32°C (40-90°F). Wear protective equipment during cleanup.			
• •	Care should be taken to ensure that the material or its containers are			
Waste Disposal	disposed of in an approved facility, in accordance with state, provincial			
	and local regulations.			
Special Shipping Instructions	DO NOT FREEZE			
Special Shipping Instructions	DONOTINELZE			

Recycled Recyclable

 1.800.810.1788
 Technical Support

 1.800.810.1788
 Customer Service

www.firestop.com email: firestop@firestop.com Passive Fire Protection Partners 1412 Derwent Way Delta, BC V3M 6H9

© 2017 PFP Partners. All rights reserved.

PFP0917-1



REGULATION INFORMATION WHMIS Not controlled HMIS Health 1, Flammability 0, Reactivity 0 **TDG Regulation** Not classified as a hazardous material **TSCA** All ingredients of this product are on the inventory list. DSL All ingredients of this product are on the list. PREPARATION INFORMATION Prepared by Chemical Laboratory, Passive Fire Protection Partners Date of Issue January 03, 2003 Telephone (604) 515-1788 Website www.firestop.com Reason for Revision Formulation reviewing, rev 001, March 22, 2003 New format of MSDS, rev 002, September 10, 2004 Ingredient information updating, rev 003, November 10, 2006 Formulation updating, rev 004, August 24, 2009 Spelling mistake on Section of Precaution fro Safe Handling and Use, rev 005, March 1, 2010 MSDS format change, rev 006, September 24, 2012 **Revision Date** September 22, 2014 Abbreviations Used % (wt.) = Weight Percentage ACGIH = American Conference of Governmental Industrial Hygienists **CAS Number =** Chemical Abstracts Series Number DSL = Domestic Substance List in Canada H = Hours HMIS = Hazardous Material Identification System **IARC** = International Agency for Research on Cancer LC₅₀ = Lethal Concentration, 50% LD₅₀ = Lethal Dose, 50% **MSHA** = Mine Safety and Health Administration N/A = Not Applicable or Not Available N/E = None Established **NIOSH =** The National Institute for Occupational Safety and Health **NTG** = National Toxicology Program **OSHA** = The Occupational Safety and Administration STEL = Short Term Exposure Limit

This information is provided in good faith and is correct to the best of PFP Partners' knowledge as of the date hereof; however, PFP Partners makes no representation as to its completeness or accuracy. Customers are encouraged to make their own determination as to the suitability of this product for their purpose prior to use. PFP Partners disclaims responsibility for damages of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.

TLV = Threshold Limit Value

TDG = Transportation of Dangerous Goods

TSCA = Toxic Substance Control Act in US

WHMIS = Workplace Hazardous Material Identification System

VOC = Volatile Organic Compounds

Recycled Recyclable



1.800.810.1788Technical Support1.800.810.1788Customer Service

© 2017 PFP Partners, All rights reserved

www.firestop.com email: firestop@firestop.com Passive Fire Protection Partners 1412 Derwent Way Delta, BC V3M 6H9