

Safety Data Sheet (SDS) OSHA Haz Com Standard 29 CFR 1910.1200.

Revision Date: 01/06/2015

Version: 1.0

Replaces Version:

SECTION 1: PRODUCT AND COMPANY INDENTIFICATION

Product Name:	4800DW	Product Code:	DW1, DW2, DW4, DW9
Product Type:	Endothermic Sealant	Use:	Firestopping Sealant
Chemical Family: Organic/Inorganic			

Company Address:

Passive Fire Protection Partners 1412 Derwent Way Delta, BC V3M 6H9 Canada

Contact Information: Telephone: 800.810.1788 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.firestop.com

SECTION 2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION

Physical Hazards:	None	
Oral:	Not Classified	
Dermal:	Not Classified	
Inhalation:	Not Classified	
Skin Corrosion / Irritation:	Not Classified	
Serious Eye Damage / Eye Irritation:	Not Classified	
Respiratory or Skin Sensitization:	Not Classified	
Germ Cell Mutagenicity:	Not Classified	
Carcinogenic:	Not Classified	
Reproductive Toxicology:	Not Classified	
Target Organ System Toxicity - Single Exposure:	Not Classified	
Target Organ System Toxicity - Repeated Exposure:	Not Classified	
Aspiration Toxicity:	Not Classified	

ENVIRONMENTAL HAZARDS

Hazards to the Aquatic Enviroment:	Not Classified
Acute Aquatic Toxicity:	Not Classified
Chronic Aquatic Toxicity:	Not Classified
Bioaccumulation Potential:	Not Classified
Rapid Degradability:	Not Classified

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS:

Hazard Symbols:	None	
Precautionary Statements:		
	D102 Keen Out Of Deech	of Chi

P102 - Keep Out Of Reach of Children P264 - Wash Hands Throughly After Handling




1.800.810.1788 Technical Support 1.800.810.1788 Customer Service

© 2015 PFP Partners. All rights reserved.

www.firestop.com email: firestop@firestop.com

Passive Fire Protection Partners 1412 Derwent Way Delta, BC V3M 6H9

OSHA Haz Com Standard 29 CFR 1910.1200.



SECTION 3. COMPOSITION /INFORMATION ON INGREDIENTS

Hazardous Components	CAS NUMBER	Precentage %*
Calcuim Carbonate	1314-65-3	< 50
Vinyl Acetate Polymer	Not disclosed	< 40
Water	7732-18-5	< 25
Auxiliary Chemicals	None known	< 5
iron Red Oxide	1309-37-1	< 0.5

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protection.

SECTION 4. FIRST AID MEASURES

Inhalation:	Move to fresh air in case of accidential inhalation of vapours.
Skin contact:	Wash affected area immediately with soap and water.
Eye contact:	Immediatel flush eyes with plenty of water for at least 15 minutes. If symptoms develop and persist, get medical attention.
Ingestion:	Consult a physician if necessary.
Symptoms:	See Section 11.

SECTION 5. FIRE FIGHTING MEASURES

Flash point:	Not applicable
Autoignition temperature:	Not available
Flammable / Explosive limits - lower:	Not available
Flammable / Explosive limits - upper:	Not available
Extinguishing media:	All standard firefighting procedures
Special firefighting procedures:	Do not breathe combustion gases. Wear protective equipment
Unusual fire or explosion hazards:	None known
Hazardous combustion products:	Carbon Dioxide (CO ₂), Carbon monoxide (CO), Fragmented Hydrocarbons

SECTION 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow to enter drains, surface or ground water.		
Clean-up methods:	Wipe up spills to prevent footing hazard. Scrape up spilled material and place in a closed container for disposal. Wear appropriate protective equipment and clothing during clean-up.		



 1.800.810.1788
 Technical Support

 1.800.810.1788
 Customer Service

www.firestop.com email: firestop@firestop.com Passive Fire Protection Partners 1412 Derwent Way Delta, BC V3M 6H9

© 2015 PFP Partners. All rights reserved.

PFP0615-1



Revision Date: 01/06/2015

Replaces Version:

SECTION 7. HANDLING AND STORAGE

Handling:

Storage:

Eye / Face protection:

Skin protection:

Avoid contact with eyes, skin and clothing. Keep out of the reach of children.

Store between 4°C (40°F) and below 32°C (90°F). Keep from freezing. Store in accordance with local regulations. Store in original container protected from direct sunlight, in a cool, dry area. Keep containers closed when not in use. Do not store in unlabled containers.

For information on product shelf life, please review labels on containers or check the Technical Data Sheet.

Version: 1.0

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Components	ACGIH	OSHA	AIHA	OTHER
Calcuim Carbonate	10 mg/m³ TWA (total dust)	5 mg/m ³ PEL (respirable fraction) 15 mg/m ³ PEL (total dust)	None	None
Iron Red Oxide	5 mg/m³ TWA (total dust)	10 mg/m³ TWA (fume)	None	None
Engineering controls: Use general ventilation and use local exhaust, where possible, in confined or enclosed				

Use general ventilation and use local exhaust, where possible, in confined or enclosed space.

Respiratory protection: Not normally required. Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Safety goggles or safety glasses with side shields.

Chemical resistant, impermeable gloves; Neoprene, Butyl-rubber, or Nitrile-rubber gloves.

Recycled Recyclable



1.800.810.1788Technical Support1.800.810.1788Customer Service

© 2015 PFP Partners. All rights reserved.

www.firestop.com email: firestop@firestop.com Passive Fire Protection Partners 1412 Derwent Way Delta, BC V3M 6H9

Revision Date: 01/06/2015

Version: 1.0

Replaces Version:



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Pasty
Color:	Red
Odor:	Mild, aromatic
Odor threshold:	Not available
pH:	8.0 - 9.0
Vapor pressure:	18.52 mm Hg
Boiling point/range:	> 100°C (> 212°F)
Melting point/range:	Not available
Specific gravity:	1.40 - 1.50 at 25°C (77°F)
Vapor density:	Heavier than air, (Air = 1)
Flash point:	Not applicable
Flammable / Explosive limits - lower:	Not applicable
Flammable / Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Evaporation rate:	< 1
Solubility in water:	Not applicable
Partition coefficient (n-octanol/water):	Not applicable
VOC content:	32.5 g/l (calculated)

SECTION 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Not applicable
Hazardous decomposition products:	Carbon Dioxide, Carbon Monoxide
Incompatible materials:	Strong Alkalis and Mineral acids.
Reactivity:	Not applicable
Conditions to avoid:	Do not freeze

SECTION 11. TOXICOLOGICAL INFORMATION

Relevant Routes of Exposure:	Inhalation, Sk	in Contact, I	Eyes, Ingestion	
Potential Health Effects / Symptoms				
Inhalation:	May cause irritation to nose and throat			
Skin contact:	May cause slight irritation of skin.			
Eye contact:	May cause slight irritation to eyes on contact.			
Ingestion:	Not expected to be harmful by ingestion. Ingestion of large amounts may produce gastrointestinal distrubances including irritation, nausea and diarrhea.			
Hazardous Components	NTP Car	cinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Calcuim Carbonate		0	No	No
Iron Red Oxide	N	0	No	No
Hazardous Components	nents Health Effects / Target Organs		Target Organs	
Calcuim Carbonate		No Data		

SDS - 4800DW



Iron Red Oxide

1.800.810.1788 Technical Support 1.800.810.1788 Customer Service www.firestop.com email: firestop@firestop.com **Passive Fire Protection Partners** 1412 Derwent Way Delta, BC V3M 6H9

No Data

© 2015 PFP Partners. All rights reserved.



Revision Date: 01/06/2015

Version: 1.0

Replaces Version:

SECTION 12. ECOLOGICAL INFORMATION

Ecological information:

Not applicable

SECTION 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only:

Recommend method of disposal:	Dispose should be in accordance with applicable regional, national, Federal, State and local governmental regulations.
Waste disposal:	The generation of waste should be avoided or minimized wherever possible. Empty containers may retain some product residues. This material and its containers must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product should at all times must comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Hazardous waste number:	It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

SECTION 14. TRANSPORT INFORMATION

Requlatory Information	UN Number	Proper Shipping Name	Classes	PG*	Label	Additional Information
DOT Classification	Not regulated	-	-	-	-	-
TDG Classification	Not regulated	-	-	-	-	-
Mexico Classification	Not regulated	-	-	-	-	-
ADR / RID Class	Not regulated	-	-	-	-	-
IMDG Class	Not regulated	-	-	-	-	-
IATA-DGR Class	Not regulated	-	-	-	-	-

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Water Transportation (IMO/IMDG)	
Proper shipping name:	Not regulated
Hazard class or division:	None

Hazard class or division:	None
Identification number:	None
Packing group:	None



1.800.810.1788 Technical Support 1.800.810.1788 Customer Service

www.firestop.com email: firestop@firestop.com

Passive Fire Protection Partners

1412 Derwent Way Delta, BC V3M 6H9

Safety Data Sheet (SDS)

OSHA Haz Com Standard 29 CFR 1910.1200.

Revision Date: 01/06/2015 Version	n: 1.0 Replaces Version: PFPPartners
SECTION 15. REGULATORY IN	IFORMATION
United States Regulatory Information	
TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory
TSCA 12 (b) Export Notification:	None above reporting de minimus
CERCLA / SARA Section 302 EHS:	None above reporting de minimus
CERCLA / SARA Section 311/312:	Immediate health
CERCLA / SARA 313:	None above reporting de minimus
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present. No California Proposition 65 listed chemicals are know to be present
Canada Regulatory Information	
CEPA DSL / NDSL Status:	All components are listed on or exempt from listing on the Canadian Domestic Substances List.
WHMIS hazard class:	Not controlled

SECTION 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections:

Prepared by:	Chemical Laboratory
Issue date:	June 1, 2015

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, PFP Partners does not assume responsibility for any results obtained by persons over whose methods PFP Partners has no control. It is the user's responsibility to determine the suitability of PFP Partners's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of PFP Partners 's products. In light of the foregoing, PFP Partners specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of PFP Partners 's products. PFP Partners further disclaims any liability for consequential or incidental damages of any kind, including lost profits.



1.800.810.1788 Technical Support 1.800.810.1788 Customer Service

www.firestop.com email: firestop@firestop.com Passive Fire Protection Partners 1412 Derwent Way Delta, BC V3M 6H9

© 2015 PFP Partners. All rights reserved.